

Don't take chances with flat house wraps. **BLOCK-IT® House Wrap** features a patented water channeling technology that delivers over **98% water drainage efficiency**. Not only does it provide 20% greater water holdout than Tyvek® HomeWrap® product†, it's also 40% stronger‡.

Protect your house and your reputation with **BLOCK-IT®**. Visit **BLOCK-IT.com** for a free sample of **BLOCK-IT® House Wrap**.



For more information including the full ICC-ES report, complete warranty and installation guidelines, visit:

www.BLOCK-IT.com • 1-844-BLOCK-IT
Kimberly-Clark Global Sales, LLC,
Roswell, GA 30076

† In the U.S. market. ‡ According to industry standard testing when comparing sample means.

©/™ Trademarks of Kimberly-Clark Worldwide, Inc. or its affiliates. Marques déposées de Kimberly-Clark Worldwide, Inc. ou de ses filiales. © KCWW. Tyvek® HomeWrap® are registered marks owned by E.I. du Pont de Nemours & Co. Photo is not representative of actual water protection. T74VUG 5/17

BLOCK-IT® Seam Tape

Create a complete weatherization envelope for your construction projects. Use **BLOCK-IT® Seam Tape** with **BLOCK-IT® House Wrap**.

- Aggressive acrylic adhesive bonding strength
- Aggressive adhesive designed to work with the drainage capabilities of our **BLOCK-IT® House Wrap**
- 3.0 mil thickness delivering one of the strongest house wrap tapes in the market
- Easy-tear technology
- 1.89" x 164' / 12 rolls per case
- 2.83" x 164' / 8 rolls per case



BLOCK-IT® Flashing Tape

BLOCK-IT® Flashing Tape contains polyolefin fabric with a butyl adhesive.

- Seamless protection against moisture during construction and after siding is installed
- Prohibits water infiltration, air conditioning and heat loss around door and window openings
- Long-term adhesion to a variety of surfaces including OSB and other standard building substrates
- Exceptional nail sealability
- Aggressive butyl adhesive
- Meets AAMA711-07 strength requirements
- 4" x 75' / 12 rolls per case
- 6" x 75' / 6 rolls per case



BLOCK-IT® Flex Flashing Tape

BLOCK-IT® Flex Flashing Tape with butyl adhesive is ideal for exterior flashing construction applications.

- Conforms to angled and contoured surfaces
- Seamless protection against moisture infiltration
- Long-term adhesion to a variety of surfaces including OSB, anodized aluminum, vinyl, plywood and concrete
- Exceptional nail sealability
- Meets requirements of AAMA 711-13
- 6" x 75' / 4 rolls per case
- 9" x 75' / 2 rolls per case



WHEN WATER STRIKES, WILL YOUR FLAT HOUSE WRAP BE UP TO THE CHALLENGE?

BLOCK-IT® House Wrap gives you superior water drainage efficiency over any other competitive drain wrap¹ at mainline pricing.



Kimberly-Clark BLOCK-IT* House Wrap An Evolution in Building Protection

Why use house wrap technology that hasn't changed in years, when you can get outstanding performance, customer satisfaction and immediate cost savings with BLOCK-IT* House Wrap?

Don't settle for the same old house wrap. Protect your structures, your reputation and your customers' investment with the right choice – BLOCK-IT* House Wrap from Kimberly-Clark, the moisture protection leader that refined and perfected breathable materials.

Builders and Contractors

The quality of the structures you build is only as good as the weatherization products you choose. When you choose Kimberly-Clark BLOCK-IT* House Wrap, you not only get an evolution in water drainage, breathability and durability, you also get savings upfront.

Most importantly, BLOCK-IT* House Wrap gives you and your customers peace of mind, with performance you can count on from a company trusted by billions of people. And, it's all backed by our 10-Year Limited Warranty.


Installers

Make installation hassles a thing of the past. BLOCK-IT* House Wrap resists tears, abrasions, punctures, and doesn't snag on tools or nails. It's quick and easy to install and provides a non-slip surface, even when wet. Plus, it's self-sealable around nails, meaning water will not infiltrate through openings, even without cap nails.

BLOCK-IT* House Wrap made by Kimberly-Clark can be used to help meet the infiltration rates of the ENERGY STAR Qualified Homes, Version 3, National Program Requirements.



Kimberly-Clark BLOCK-IT* House Wrap prevents the penetration of water and channels water away from your structure, while providing a breathable barrier technology that will help protect your building for years to come.

- Drainage Wrap**
 BLOCK-IT* House Wrap is a drainage wrap, eliminating the need for a specialty wrap and is approved for commercial buildings 4 stories and below.
- Exclusive Patented Water Channeling Technology**
 BLOCK-IT* House Wrap channels over 98% of water away from the wall assembly and onto the ground.
- Moisture Vapor Transmission**
 BLOCK-IT* House Wrap provides excellent breathability, allowing vapors to escape from the wall cavities to help prevent water damage.
- Strong**
 BLOCK-IT* House Wrap is 40% stronger than the leading brand.
- Ideal Air/Water Holdout and Perm Rating**
 BLOCK-IT* House Wrap technology helps prevent moisture and air from leaking into your structure.
- Premium UV Performance**
 BLOCK-IT* House Wrap is made with UV inhibitors that provide premium UV protection for up to 6 months.
- Surfactant Resistance**
 BLOCK-IT* House Wrap protects your structure from oils and powerwashing soap solutions.
- Durable**
 BLOCK-IT* House Wrap resists tears, abrasions and punctures. It does not snag on nails or equipment.
- Made in the USA** 

Kimberly-Clark BLOCK-IT* House Wrap meets the following requirements when installed according to Kimberly-Clark BLOCK-IT* House Wrap installation instructions: ICC-ES AC38 Water Resistive Barrier, ASTM E2273 Drainage Efficiency of Exterior Insulation and Finish Systems Clad Wall Assemblies and ASTM E2178 Air Permeance of Building Materials.

FEATURES	BENEFITS
Water Barrier	Tough barrier layer helps prevent water penetration and assists with maintaining dry building structure.
Exclusive Patented Channeling Technology	Unique channeling feature directs liquid away from the wall assembly and to the ground. Passes challenging ASTM E2273 Drainage Test. Provides premium performance at mainline pricing.
Breathability	Patented breathable barrier technology allows water vapor to escape from the structure.
High Durability Materials	Barrier can be maintained over time – from installation to extended use – due to excellent resistance to tears, abrasion and punctures. 6-month UV stability.
Additional Product Innovation	Non-slip even when wet. More of a material feel than paper. Does not snag on nails, tools or equipment. GREENGUARD Gold certified.

Technical Data – ICC-ES Evaluation Report ESR-3641

Water Resistive Barrier	AC38	Pass
Drainage Efficiency	ASTM E2273	> 98%
Tensile Strength (Grab)	ASTM D5034	Pass
WVTR (Perms)	ASTM E96	15
Water Resistance	ASTM D779	Pass
Surface Burning	ASTM E84	Class A (Spread and Smoke)
UV Exposure Rating	Days	6 months

Roll Sizes: 3' x 100' 9' x 75'
 5' x 100' 9' x 150'
 9' x 100' 10' x 100'
 10' x 150'

